



**Globe Pipe Hanger Products Inc.**

14601 Industrial Parkway

Cleveland, OH 44135 USA

Phone: 216-362-6300, Fax: 216-267-6884

sales@globepipehanger.com

**Product Type:** [SilverHawk Top Beam Clamps](#)

**Product Name:** [SilverHawk 100 Series Top Beam Clamp #103- 101S](#)

**Product Summary**

**SIZE RANGE:**

3/8" rod sizes.

**MATERIAL:**

Cold rolled steel with a plated hardened cup point set screw and lock nut.

**FINISH:**

Electro-plated zinc

**ORDERING:**

Specify 103-101S SilverHawk

**INSTALLATION:**

Must install in an upright position.

Torque Value = 60 in-lbs

When a torque wrench is not available, the setscrew should be tightened so it contacts the I-beam and then add an additional 1/4 to 1/2 turn.

Made in U.S.A. Patent Pending.

A: 3/8 inch

B: 1 3/16 inches

C: 1 5/8 inches

D: 17/32 inches

E: 3/4 inch

F: 3/8 inch (min.)

G: 15/16 inches

Max. Recommended Load: 400 lbs.

**Approvals**

UL Listed for top of Beam. FM Approved for NFPA 13, maximum rated pipe size. Complies with Manufacturers Standardization Society SP-69 (Type 19 & 23), and federal specification WW-H-171E.

**Function**

Recommended for attaching hanger rod to top or bottom flange of a beam or bar joist, where the thickness of a joist or flange does not exceed 3/4 inch. The open back design permits rod adjustment and visual verification during installation.