



Product Type: [SilverHawk Top Beam Clamps](#)

Product Name: [SilverHawk 100 Series Top Beam Clamp #103- 101S](#)

Product Summary

SIZE RANGE:
3/8" rod sizes.

MATERIAL:
Cold rolled steel with a plated hardened cup point set screw and lock nut.

FINISH:
Electro-plated zinc

ORDERING:
Specify 103-101S SilverHawk

INSTALLATION:
Must install in an upright position.
Torque Value = 60 in-lbs
When a torque wrench is not available, the setscrew should be tightened so it contacts the I-beam and then add an additional 1/4 to 1/2 turn.

Made in U.S.A. Patent Pending.

A: 3/8 inch
B: 1 3/16 inches
C: 1 5/8 inches
D: 17/32 inches
E: 3/4 inch
F: 3/8 inch (min.)
G: 15/16 inches
Max. Recommended Load: 400 lbs.

Approvals

UL Listed for top of Beam. FM Approved for NFPA 13, maximum rated pipe size. Complies with Manufacturers Standardization Society SP-69 (Type 19 & 23), and federal specification WW-H-171E.

Function

Recommended for attaching hanger rod to top or bottom flange of a beam or bar joist, where the thickness of a joist or flange does not exceed 3/4 inch. The open back design permits rod adjustment and visual verification during installation.