



**Product Type:** [SilverHawk Top Beam Clamps](#)

**Product Name:** [SilverHawk 100 Series Top Beam Clamp #103- 101S](#)

**Product Summary**

**SIZE RANGE:**  
3/8" rod sizes.

**MATERIAL:**  
Cold rolled steel with a plated hardened cup point set screw and lock nut.

**FINISH:**  
Electro-plated zinc

**ORDERING:**  
Specify 103-101S SilverHawk

**INSTALLATION:**  
Must install in an upright position.  
Torque Value = 60 in-lbs  
When a torque wrench is not available, the setscrew should be tightened so it contacts the I-beam and then add an additional 1/4 to 1/2 turn.

Made in U.S.A. Patent Pending.

**SIZE RANGE:**  
3/8" rod sizes.

**MATERIAL:**  
Cold rolled steel with a plated hardened cup point set screw and lock nut.

**FINISH:**  
Electro-plated zinc

**ORDERING:**  
Specify 103-101S SilverHawk

**INSTALLATION:**

Must install in an upright position.

Torque Value = 60 in-lbs

When a torque wrench is not available, the setscrew should be tightened so it contacts the I-beam and then add an additional 1/4 to 1/2 turn.

Made in U.S.A. Patent Pending.

### **Product Attributes**

A: 3/8 inch

B: 1 3/16 inches

C: 1 5/8 inches

D: 17/32 inches

E: 3/4 inch

F: 3/8 inch (min.)

G: 15/16 inches

Max. Recommended Load: 400 lbs.